

# Desktop Label Printer LK-B20

## High quality desktop label printer

Direct thermal & Thermal transfer  
Large media / Ribbon capacities  
Fast print speed  
Easy to load media and ribbon  
Various connectivity option  
Peel-off & Auto-cutter option  
Compact desktop design

Easy to load media and ribbon



## LKB SERIES SPECIFICATION



<b>MODEL</b>		LK-B20
<b>PRINT METHOD</b>		Thermal Transfer and Direct Thermal
<b>PRINTING SPEED(max)</b>		152mm/sec
<b>PRINT WIDTH(max)</b>		104mm
<b>PRINT LENGTH(max)</b>		630mm
<b>RESOLUTION</b>		203dpi, 8 dot/mm
<b>PAPER WIDTH(min ~ max)</b>		38 ~ 118mm
<b>PAPER ROLL SIZE(max)</b>		127mm
<b>PAPER THICKNESS</b>		0.06 ~ 0.18mm
<b>PAPER TYPE</b>		Label, Tag, Continuous, Fanfold
<b>PAPER SENSOR</b>		Label gap, Notch, Black Mark
<b>RIBBON WIDTH (Outside diameter)</b>		33mm to 110mm
<b>RIBBON LENGTH</b>		300M, $\phi$ - 74mm
<b>INTERFACE</b>	<b>STANDARD</b>	Parallel (IEEE-1284), USB
	<b>OPTION</b>	Ethernet, Wireless LAN 802.11b, Serial
<b>MEMORY</b>	<b>STANDARD</b>	8MB SDRAM, 5MB Flash
	<b>OPTION</b>	8MB Flash
<b>SERIAL BAUD RATE</b>		38,400 bps(Max)
<b>AUTO CUTTER (OPTION)</b>	<b>LIFE</b>	1,000,000 cuts
	<b>TYPE</b>	Guillotine
<b>PEELER</b>		Option
<b>PROGRAMMING</b>		EPL II (Eltron Programming Language), ZPL
<b>BARCODE</b>	<b>1D</b>	Code 39, Code 128 with subsets A/B/C, Code 93, Codabar
		Interleaved 2 of 5, UPC-A and UPC-E with 2or5 digit extensions
		EAN-8 and EAN-13 with 2or5 digit extensions, Postnet, Plessey
<b>2D</b>	German Post Code, MSI-3	
	MaxiCode, PDF 417, QR Code, DataMatrix	
<b>FONT SPECIFICATION</b>		5 bitmapped (8x12, 10x16, 12x20, 14x24, 32x48)
<b>WEIGHT(kg)</b>		3.6kg
<b>SIZE (W x D x H)mm</b>		215 x 287 x 231

Specifications are subject to change without notice.

January 2007

