

## HT- 4000/2000 Series SPECIFICATIONS

Function	HT- 4212	HT-2212
Processor	Intel Celeron 2.0 GHz	AMD NX 1100
Memory	Default 256MB Expandable to 2GB DDR Memory 2 DIMM Sockets	Default 128 MB Expandable to 2GB DDR Memory 2 DIMM Sockets
Video memory	16MB - 128MB Shared with system memory	
Display	12.1" TFT LCD 800 x 600, 180 nits Upgradable to 350 nits	
Tilt adjustment	From 42.5° to 77.5°	
Touch sensor	Resistive type	
Touch resolution(optional)	1024 X 1024, Mouse emulation	
<b>Expansion</b>		
PCI slot	1 X	
Condition	PCI slot is occupied & not available while powered USB control card is installed.	N/A
Hard disk drive (Ultra DMA)	40GB	20GB
2nd HDD	2.5", OPTIONAL	
Power management kit	OPTIONAL	INCLUDED
Main features	1. Power-off prevention software 2. Uninterruptible power supply 3. CR port control	
Integrated battery backup	UPS Battery must be purchased separately	
<b>Connectivity</b>		
Powered USB ports (12V/24V powered)	Proprietary control card, OPTIONAL	N/A
USB ports	3 X	6 X
RS232 ports	4 X	2 X
VGA port	1 X	
Stereo audio out / mic in	YES	
Ethernet 10/100 (onboard LAN)	YES	
Parallel port	1 X	
PS/2 KB & MOUSE	YES	
Cash drawer port (CR PORT)	1x, optional (included in power management kit)	1 X
Operating systems	Win 2000 / XP Professional / WEPOS	
Color options	Charcoal / Ivory white	
<b>Physical dimensions</b>		
Terminal	270mm(W)x240mm(D)x102.5mm(H)(10.6" X9.5" X4.0" )	
Display	288 mm(W)x130.5mm(D)x255 mm(H)(11.3"x5.1"x8.9")	
Weight	6.5 kgs (14.3 lbs.)	5.45 kgs (12 lbs.)
Electrical requirements	Switching power supply: Input 115/230V, output DC 180W	AC adaptor: Input 100~240V, output DC 12V/80W
Safety certifications	PSU: UL/TUV mark Terminal: FCC,CE (class A)	
<b>Optional peripherals</b>		
SD-300	USB Interface. 2-in-1 MSR and finger print sensor; MSR is UPOS 1.8 compliant (MSR/FP Optional)	
BC-200	Infrared Bar Code reader, USB interface	
PD-2601	2x20 VFD customer display, 5x7 dots matrix RS232 interface default (USB interface optional)	2x20 VFD customer display, 5x7 dots matrix USB interface default (RS232 interface optional)

Information and specifications in this catalogue are subject to change without notice.

**POSIFLEX**  
Your Success is Our Vision

**hybrid**  
POS



## Hybrid POS Terminal HT- 4000/2000 Series

Flexible and High Performance POS Solutions from POSIFLEX

**POSIFLEX**

1280 San Luis Obispo Avenue  
Hayward, California 94544 USA  
e-mail: sales@posiflexusa.com

Tel:510.429.7097  
Fax:510.475.0982  
www.posiflexusa.com



2005 USA.V.01



## Hybrid POS Terminal HT- 4000/2000 Series

- Intuitive POS terminal design
- Touch or keyboard configuration
- Screwless and spill-proof architecture
- PC POS Box featuring an adjustable 12.1" TFT LCD and Elo Touch Panel
- Effective cable management design
- Power guard feature with software controlled power switch to prevent accidental shutdown of system



HT Bundle in Ivory White

HT System in Charcoal



MSR 2-in-1 Attachment with optional finger print sensor (SD-300)



Ergonomic design allows LCD display swivel angle 0° to 16° in clockwise direction for improved viewing angles



A patented finger release lever " Gear Lock " mechanism easily adjusts the LCD tilt angle from 42.5 ° to 77.5 °



Cable management design allows easy routing of cables for aesthetic and reliability purposes

## Available peripherals



Cash Drawer (CR Series)



POS Programmable Keyboard (KB Series)



POS Printer (AURA/PP Series)



Customer Pole Display (PD-2601)

## Hybrid POS Terminal HT-4000/2000 Series

Designed for retail environments and applications that require a compact system powerful enough to meet all POS application market demands.

